

WO2006040577

Publication Title:

PUSH BUTTON ASSEMBLY

Abstract:

Abstract of WO2006040577

A push button assembly comprises a button (1) with an actuating structure (5) movably mounted within a housing (2) for operation of a switch (20). The housing (2) provides a frame (18) comprising side wall structures (16), with a flange structure (15) mounted at a top open end thereof. The axial length of the housing (2) is shorter than the horizontal length of the side wall structures (16), resulting in a short push button assembly. The button (1) is illuminable via a lamp (25) which is provided on a carrier strip (22), the switch (20) being mounted on a body (19), both of which can be removably mounted substantially within the confines of the housing (2), with respective connection terminals (23, 21) projecting outward thereof, the assembly therefore occupying minimal space behind a panel when mounted on such a panel of an amusement or gaming machine where space may be restricted.

Data supplied from the esp@cenet database - Worldwide d30

Courtesy of <http://v3.espacenet.com>

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 April 2006 (20.04.2006)

PCT

(10) International Publication Number
WO 2006/040577 A1

(51) International Patent Classification:
H01H 13/02 (2006.01) *H01H 9/18* (2006.01)

[GB/GB]; Horley Mill, 83 Lee Street, Horley, Surrey RH6 8HD (GB).

(21) International Application Number:
PCT/GB2005/003970

(74) Agents: QUEST, Barry et al.; Wilson Gunn, 5th Floor, Blackfriars House, The Parsonage, Manchester M3 2JA (GB).

(22) International Filing Date: 17 October 2005 (17.10.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0422939.9 15 October 2004 (15.10.2004) GB
0422927.4 15 October 2004 (15.10.2004) GB

(71) Applicant (for all designated States except US): GAMES-MAN LIMITED [GB/GB]; Crompton Fields, Crompton Way, Crawley, West Sussex RH10 2QR (GB).

(72) Inventor; and


(75) Inventor/Applicant (for US only): COVE, James

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: PUSH BUTTON ASSEMBLY



(57) Abstract: A push button assembly comprises a button (1) with an actuating structure (5) movably mounted within a housing (2) for operation of a switch (20). The housing (2) provides a frame (18) comprising side wall structures (16), with a flange structure (15) mounted at a top open end thereof. The axial length of the housing (2) is shorter than the horizontal length of the side wall structures (16), resulting in a short push button assembly. The button (1) is illuminable via a lamp (25) which is provided on a carrier strip (22), the switch (20) being mounted on a body (19), both of which can be removably mounted substantially within the confines of the housing (2), with respective connection terminals (23, 21) projecting outward thereof, the assembly therefore occupying minimal space behind a panel when mounted on such a panel of an amusement or gaming machine where space may be restricted.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report

-1-

PUSH BUTTON ASSEMBLYTECHNICAL FIELD

The invention relates to push button assemblies and is particularly though not exclusively concerned with a push button assembly for use
5 within an amusement or gaming machine.

BACKGROUND ART

A push button assembly as used with an amusement or gaming machine typically comprises a push button, a housing, a lamp and switch unit, and an actuating structure with a spring.

10 GB 2350722 A discloses a push button assembly of this kind. The push button comprises a translucent disc, a transparency and a fitted lens cap. The housing is an open ended tubular structure with a flange around one end defining a bezel. The push button is movably retained within the flange and the lamp and switch unit is attached removably to the opposite
15 open end of the housing so that the lamp is within the housing for illumination of the button and the switch is outside the housing. The actuating structure comprises a hollow stem with at least one hooked finger which is located in the housing between the push button and the switch. The tubular structure of the housing is threaded. In use the tubular structure
20 is passed through an aperture in a panel of the machine with the flange on the outside and a nut is screwed onto the tubular structure against the underside of the panel to hold the housing firmly attached to the panel.

With this known push button assembly the length beneath the panel which includes the lamp and switch unit is relatively large. This can be a
25 problem in machines where there is little space behind the panel.

-2-

An object of the present invention is to provide a push button assembly which can be made with reduced length so as to be suitable for use where space for installation is restricted.

DISCLOSURE OF THE INVENTION

5 According to the invention therefore, there is provided a push button assembly comprising a housing with an open end thereto bounded by a flange structure, the housing being insertable through an aperture in a panel with the flange on an outer side thereof, a fixing means for fixing the housing relative to the panel beneath the panel, a push button movably
10 mounted within the open end and flange structure, a lamp mountable relative to the housing for illuminating the button, a switch mountable relative to the housing for operation by movement of the button via an actuating structure disposed between the button and the switch within the housing, characterised in that the lamp and the switch are mounted within the
15 housing so that at least a major part of the lamp and the switch is located within the confines of the housing.

With this arrangement, the push button assembly beneath the panel can be of reduced length since the lamp and the switch are incorporated in the housing rather than being attached thereto substantially externally of the
20 housing. Less space may therefore be needed for installation beneath the panel.

Preferably the housing has a generally open square frame structure comprising side wall structures with the flange structure mounted at one end. Alternatively the frame structure may be generally rectangular or
25 circular or polygon in shape. The housing may provide abutments for

-3-

supporting the actuating structure. Preferably one of the side wall structures may be generally open to provide access to the interior of the housing. The frame structure is preferably shorter in axial length than the horizontal length of each of the side wall structures.

- 5 Preferably also, the flange has outwardly inclined side walls which taper towards the top free end. The flange is preferably opaque.

 The flange structure may comprise a downwardly projecting skirt part defining a peripheral gap between the side wall structures and said skirt part. The skirt part may be light-transmitting. The skirt part may provide an
10 illuminable boundary. The boundary may be illuminable by an illumination means disposed in said gap. The illumination means is preferably in the form of multiple LEDs on a printed circuit board. The housing frame 18 may pass through an aperture in said board. The LEDs are preferably independently operable from said lamp and/or each other.

- 15 The independently operable LEDs may be operable together in a static or flashing arrangement to give the effect of a "halo" around the button. Alternatively they may be operable in any sequence to display points of light around the boundary.

 This provides an additional illumination arrangement where the
20 boundary may be lit alone or with the lamp to indicate a different button status. Additionally or alternatively the illumination of the boundary may be operable in a non-play mode to attract players.

 The housing may provide electrostatic protection to any circuitry within said housing by providing "grounding members" which make contact with the
25 panel which is also conductive and connected to the ground, to discharge any

-4-

introduced electrical charges. In this respect, a gaming machine housing may have low conductivity properties or there may be a printed "circuit" which leads across the panel to the housing which is grounded itself or which has an earthing/grounding component fixed thereto. This prevents spurious and
5 fraudulent actuation of the button. The grounding members preferably comprise, for example, carbon conductive structures or other suitable conductive structures. In this respect, the flange is also conductive and preferably comprises a carbon conductive material.

The fixing means may comprise one or more clips provided on one or
10 more of the side wall structures, engageable with one or more holes provided in the panel. There may be pairs of spring clips on the outer sides of some or all opposing side wall structures. The or each clip may be engageable with the aperture for the housing or a hole separate thereto.

The push button may comprise the switch actuating structure,
15 mounted upon which are a translucent cover part and a translucent cap. The translucent cap may have an upwardly convex domed top wall with downwardly projecting edge walls. The cover part may have a projection on its lower surface for interaction with the spring members. The cover part and the cap may be the same in shape as the frame structure of the housing.
20 Alternatively, the cover part and the cap are the same in shape as the opening provided by the flange. There may be a transparency placed between the cap and the cover part which provides printed words and/or graphics, which may be specific to the machine.

Preferably the switch actuating structure has a generally square frame
25 with a square bottom wall provided with a centrally disposed aperture. Two

-5-

elongate legs with outwardly turned feet may be provided projecting from the centre of opposed bottom wall edges at right angles to the edges. Preferably also, the bottom wall has spring members fixed across the frame to provide the relative movement of the button within the flange structure.

- 5 Two of the opposed spring members preferably have push rods mounted in a downwardly projecting direction, which project through apertures in the bottom wall so as to be displaceable within the button.

Preferably the switch comprises a rectangular body with an upwardly projecting actuator and connector terminals. The body most preferably
10 overlies the inner side wall structures within the confines of the housing with the terminals projecting out of the housing. Most preferably the switch is a microswitch.

Preferably, the lamp is disposed in the centre of the housing and may be mounted on a rectangular strip with connector terminals. The lamp may
15 be a filament lamp but is most preferably an LED or a plurality of LEDs. The strip preferably overlies the switch within the confines of the housing with the terminals projecting out of the confines of the housing. The lamp may emit white or coloured light when energised with varying intensities.

Alternatively, the lamp may also provide an image producing
20 component such as an LCD panel, where the crystals in the LCD panel can be energised by supplying a current thereto making the individual crystals twist to allow light from the lamp through to illuminate the button with an image. Such a panel may be mounted between said lamp and said button. This will control light emitted from the lamp. Colour filters may be applied to allow
25 different colours and effects.

-6-

Alternatively still, the lamp may comprise an OLED which provides the lighting and an image producing component (Organic Light Emitting Device) wherein a series of organic layers, for example small-molecular weight or polymer-based organic materials, between two electrical contacts are applied
5 to a carrier such as glass or plastics film. The carrier may be flexible. The OLED may be instead of, or in addition to the lamp.

Preferably, the lamp strip and the switch body are separate components. Alternatively, they may be a single unit. Preferably the lamp and the switch are removably mounted within the housing and most
10 preferably the strip and the body of the lamp and the switch respectively completely within the confines of the housing. The switch body and lamp strip may snap onto a part of the housing and may be held in place by pegs which pass first through the body of the switch and then through the strip of the lamp. Alternatively, screws could be used in place of the pegs, or the
15 unit could be glued into position.

The terminals from the lamp and the switch may be connected to appropriate operating circuitry of an amusement or gaming machine. The LCD panel or OLED may also be connected to the operating circuitry of an amusement or gaming machine. The lamp can be activated in different ways
20 on different occasions which may correspond to stages in the game.

When fixed to an amusement or gaming machine the push button assembly may be mounted on a panel of the machine, which may be a glass or plastics or metal or other panel, by insertion of the housing frame through the aperture in the panel, the aforesaid spring clip or clips springing outwards
25 into position on the underside of the panel, resulting in the flange and the

-7-

push button being on the exterior of the panel, the lamp and the switch being below the panel, within the confines of the housing, except for the terminals which project downwardly for connection to the appropriate circuitry.

5 BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described further by way of example only and with reference to the accompanying drawings in which:

Figure 1 is a perspective view of one form of an assembled push button assembly in accordance with the invention;

10 Figure 2 is a diagrammatic side view of the assembly of figure 1;

Figure 3 is an exploded upright perspective view of the push button assembly; and

Figure 4 is an exploded side perspective view of the push button assembly.

15 MODES FOR CARRYING OUT THE INVENTION

As shown in figure 3 a push button assembly has a push button 1, a housing 2, a switch unit 3, and an illumination unit 4.

The push button 1 comprises a switch actuating structure 5, a translucent cover part 6 and a square translucent cap 7 having an upwardly
20 slightly convexly domed square top wall bounded by peripheral downwardly projecting edge walls.

The switch actuating structure 5 comprises a square frame 8 bounding an attached square bottom wall 9 with a central aperture 10. A push rod 12 projects downwardly from the bottom wall 9 at right angles
25 thereto in the region between the central aperture 10 and the centre part of

-8-

opposite edges of the bottom wall 9. A spring (not shown) sits around the push rod 12 which then sits within a cylinder 29 provided by the housing so the push rod is displaceable therewithin. A further rod (not shown) is provided on the opposing side of the bottom wall 9, which is positioned
5 above the switch unit 3. Centrally of two of the bottom wall edges at right angles to the aforesaid edges there are two elongate legs 13 which project downwardly from the wall at right angles thereto and terminate at their free ends in outwardly turned feet 14.

The housing 2 comprises a generally square frame 18 structure having
10 at one end an opaque peripheral flange 15 with outwardly inclined side walls tapering towards the top free end of the frame structure and peripheral side wall structures 16 depending from the underside of the peripheral flange 15. Two opposed side wall structures 16 are provided on their outer side with respective pairs of spring clips 17. One such side wall structure has fixing
15 holes therethrough. The flange 15 comprises a composite carbon material which has high resistance conductive properties.

The flange structure 15 may also comprise a downwardly projecting peripheral light-transmitting skirt part (not shown) which defines a peripheral gap between said skirt part and the side wall structures 16, so as to provide
20 an illuminable boundary. The boundary may be illuminable by a generally square printed circuit board carrying multiple LEDs around its periphery, which comprises a central aperture through which the side wall structures 16 pass, the LEDs thereby being positioned in said gap and covered by the skirt part. The LEDs are connected to appropriate circuitry on the board for operation
25 independently of one another and the lamp 25.

-9-

The housing 2 also comprises "grounding members" 15a which comprise for example carbon conductive structures with high resistance leading from the flange 15 through the illuminable skirt part and which make contact with a panel of a gaming or amusement machine. Where the panel is made of an insulating material e.g. glass or plastics, the panel has printed regions of conductive material. Where the panel is constructed of a conductive material e.g. metal such regions are not required. In both cases, the panel is earthed or grounded by a highly resistant conductive housing of the machine or other suitable earthing component, so that any electrostatic charge can be carried away from the circuitry of the assembly. This arrangement is to prevent spurious activation of the button 1 where an electrostatic charge is applied in fraudulent activities. Where the flange structure has a skirt part, these can be provided in the skirt part which contacts the panel.

The interior of the housing between the side wall structures 16 is generally open and the illumination unit 4 and the switch unit 3 are mounted within the housing 2.

The frame structure is of short axial length and in particular is shorter than the horizontal length of each side wall structure 16.

The switch unit 3 is a conventional microswitch having a rectangular body 19 with an actuator projection 20 projecting upwardly from a narrow top side body and three connector terminals 21 projecting downwardly from the opposite narrow bottom side of the body 19. The body is located within the housing 2 and overlies the inner side of the side wall structure 16b. The body 19 is contained wholly within the confines of the housing 2 and the

-10-

terminals 21 project downwardly out of the housing as shown in figure 2. The switch unit 3 is held in position by the body snapping onto a part of the moulding and pegs passing through aligned holes 22 in the side wall structure and the body 19 of the switch unit 3. Alternatively screws or
5 other means may be used to fix the switch body in position.

The illumination unit 4 comprises a lamp which is an LED 25 fixed to connection terminals 23 mounted on a supporting strip 24. The strip 24 and LED 25 are fixed within the housing 2 so as to be wholly within the confines of the housing. The strip 24 overlies the body of the switch unit 3
10 and is held in position by the aforesaid pegs which also pass through holes 22 in the strip 24. The terminals 23 project downwardly out of the housing parallel to the switch unit terminals 21. The illumination unit 4 is fixed in position with the LED 25 disposed centrally of the housing. Alternatively a plurality of LEDs which might not be centrally disposed may be used.

15 Additionally, an LCD panel (not shown) may be introduced between the lamp 25 and the button 1, where an electrical charge applied to the crystals can cause rotation of the crystals to allow light through to illuminate the button 1 from the lamp 25. Colour filters can be applied to each crystal to generate different colours of light which is dependent upon the degree of
20 rotation of the crystals and the wavelength of light passing therethrough. The LCD panel is an image producing component.

Alternatively to said lamp 25, OLEDs may be used (Organic Light Emitting Device) which provides the lighting and an image producing component. The OLED comprises a film having a series of organic polymers
25 and or low molecular weight organic compounds which are light emitting,

-11-

positioned between two electrodes which is applied to a carrier substrate such as glass or flexible plastics material. The electrodes can be connected to the circuitry of the amusement or gaming machine for control. The film can be inserted between the button 1 and the housing 2.

5 The push button 1 is assembled with the housing by insertion of the frame 8 downwardly into the housing through the peripheral flange 15 so that the legs 13 slide along the inner sides of the two opposed side wall structures 16a, 16c of the frame structure. The legs 13 are springy and deflected slightly inwardly until the legs reach recesses 26 at the bottom
10 edges of the side wall structure. The feet 14 spring back into these recesses 26 to lock the frame structure in a position at which the frame is wholly within the confines of the housing. In this position the central aperture 10 fits around the lamp 25 and one of the push rods 12 is aligned with the microswitch actuation projection 20.

15 The cover part 6 sits on the frame 8 and the cap 7 sits on top of the cover part around the frame 8 and projects partially beyond the open top end of the peripheral flange 15. The cap 7 is retained within the flange 15 by interengagement with the frame 8 but is free to move through a limited distance into and out of the flange 15 being limited by abutments 27 in the
20 housing. The cover part 6 has a projecting part 28 on its lower surface.

 With this arrangement, a natural "halo" effect occurs when the lamp 25 or other button 1 lighting device, such as an OLED, is illuminated where light is emitted in a defined line between the flange structure 15 and the cap 7 of the button 1. As appreciated this may be in addition to any boundary
25 illumination halo effect as previously discussed.

-12-

The cap 7 can be pushed in with the push rod 12 pressing against the resistance of the spring to cause the opposing rod to move downwardly to actuate the microswitch 20.

5 The push button assembly can be mounted on a panel by insertion of the frame structure 18 of the housing through a hole in the panel to a position at which the peripheral flange 15 abuts inside the panel around the hole, the "grounding members" 15a thereby making contact with the panel.

The push button is held in position by the four spring clips 17 springing outwardly into position on the underside of the panel.

10 The cap 7 projects freely from the panel for manual operation and the peripheral flange 15 provides a bezel around the cap 7.

On the underside of the panel the terminals 21, 23 project freely for connection to appropriate circuitry. Other parts of the assembly do not take up much space beneath the panel and it will be noted that the assembly can
15 be fixed securely in position without requiring application of any fixing structure, or manipulation of the assembly beneath the panel.

The panel may be a screen-printed panel of a fruit machine or other amusement or gaming machine whereby the lamp terminals 23 can be connected to the usual operating circuitry so that the lamp 25 is switched on
20 with a steady or flashing light at appropriate occasions to signify that the button assembly can be used to initiate a game play procedure or event or for other purposes; and the switch terminals 21 can be connected to the usual operating circuitry to cause activating impulse to be fed thereto by operation of the push button when appropriate.

25 Furthermore, the independently operable boundary illumination,

-13-

producing a halo effect around the flange structure 15, can also produce various lighting arrangements alone or in combination with the lamp 25. For example, the boundary may be wholly or partially lit, and/or be made to flash and/or the individual LEDs may be lit to produce points of light around the
5 boundary. Alone, the steady or flashing boundary illumination may indicate a specific mode of play or may indicate an inoperable machine in a so called "attract" mode.

It is of course to be understood that the invention is not intended to be restricted to the details of the above embodiments, which is described by
10 way of example only. Thus, the boundary illumination may be effected by other suitable lighting arrangements such as the previously described OLEDs or LCD arrangements. Furthermore, alternatives to the lamp and LCD panel/OLED arrangements may include any other suitable LCD or LED technology such as cholesteric LCD's, Zenithal bistability LCD's, twisted
15 nematic LCD's (bistable and super varieties), thin film transistors, and polymer LED's to generate the illumination and/or an image producing component.

CLAIMS

1. A push button assembly comprising a housing (2) with an open end thereto bounded by a flange structure (15), the housing (2) being insertable through an aperture in a panel with the flange (15) on an outer side thereof, a fixing means for fixing the housing (2) relative to the panel beneath the panel, a push button (1) movably mounted within the open end and flange structure (15), a lamp (25) mountable relative to the housing (2) for illuminating the button (1), a switch (20) mountable relative to the housing (2) for operation by movement of the button (1) via an actuating structure (5) disposed between the button (1) and the switch (20) within the housing (2), characterised in that the lamp (25) and the switch (20) are mounted within the housing (2) so that at least a major part of the lamp (25) and the switch (20) is located within the confines of the housing (2).
2. A push button assembly according to claim 1 wherein the housing (2) has a generally open square frame structure (18) comprising side wall structures (16) with the flange structure (15) mounted at one end.
3. A push button assembly according to any one of claims 1 or 2 wherein the housing (2) provides abutments for supporting the actuating structure (5).
4. A push button assembly according to any one of claims 2 or 3 wherein at least one of the side wall structure (16) is generally open to provide access to the interior of the housing (2).
5. A push button assembly according to any one of claims 2-4 wherein the frame structure (18) is shorter in axial length than the horizontal

-15-

length of each of the side wall structures (16).

6. A push button assembly according to any one of claims 1-5 wherein the flange structure (15) has outwardly inclined side walls which taper towards the top free end of the housing (2).
- 5 7. A push button assembly according to any one of claims 1-6 wherein the flange structure (15) is opaque.
8. A push button assembly according to any one of claims 2-7 wherein the flange structure (15) comprises a downwardly projecting peripheral skirt part defining a peripheral gap between said part and the side wall structures (16).
- 10 9. A push button assembly according to claim 8 wherein the skirt part is light-transmitting.
10. A push button assembly according to claim 9 wherein the skirt part provides an illuminable boundary to give the effect of a "halo" around the button (1).
- 15 11. A push button assembly according to claim 10 wherein the illuminable boundary is illuminable by an illumination means disposed in said gap.
12. A push button assembly according to claim 11 wherein the illumination means is preferably in the form of multiple LEDs on a printed circuit board.
- 20 13. A push button assembly according to claim 12 wherein the LEDs are independently operable from said lamp (25) and/or each other.
14. A push button assembly according to any one of claims 1-13 wherein the housing (2) provides electrostatic protection to any circuitry within said housing (2).
- 25

-16-

15. A push button assembly according to claim 14 wherein the protection comprises "grounding members" integrated into said housing (2) to discharge any introduced electrical charges.
- 5 16. A push button assembly according to claim 15 wherein the "grounding members" comprise carbon conductive structures.
17. A push button assembly according to any one of claims 1-16 wherein the fixing means comprises one or more clips (17) on one or more of said side wall structures (16) engageable with holes in said panel.
- 10 18. A push button assembly according to any one of claims 1-17 wherein the switch actuating structure (5) comprises a generally square frame with a centrally disposed aperture (10) and two elongate legs (13) with outwardly turned feet (14) projecting from the centre of opposed bottom wall edges at rights angles thereto.
- 15 19. A push button assembly according to claim 18 wherein the bottom wall has spring members fixed across said frame to provide relative movement of the button (1) within the flange structure (15).
- 20 20. A push button assembly according to claim 19 wherein the spring members provide downwardly projecting push rods (12) for projection through apertures in said bottom wall so as to be displaceable within the button (1).
21. A push button assembly according to any one of claims 1-20 wherein the switch (20) comprises a rectangular body (19) with an upwardly projecting actuator and connection terminals (21).
- 25 22. A push button assembly according to claim 21 wherein the body (19) overlies the inner side wall structures (16) within the confines of the

-17-

housing (2) and the terminals (21) projecting out of said housing (2).

23. A push button assembly according to any one of claims 1-22 wherein the switch (20) is a microswitch.
24. A push button assembly according to any one of claims 1-23 wherein
5 the lamp (25) is disposed in the centre of the housing (2) mounted on a rectangular strip (22) with connector terminals (24).
25. A push button assembly according to any one of claims 1-24 wherein the lamp (25) is an LED or multiple LEDs.
26. A push button assembly according to any one of claims 1-24 wherein
10 an LCD panel is provided between said lamp (25) and said button (1) to allow control of the light.
27. A push button assembly according to claim 26 wherein colour filters are applied to the panel to allow different colours and effects.
28. A push button assembly according to any one of claims 1-23 wherein
15 the lamp (25) comprises an OLED.
29. A push button assembly according to any one of claims 21-27 wherein the lamp strip (22) and/or switch body (19) are separate components.
30. A push button assembly according to any one of claims 1-29 wherein the lamp (25) and/or the switch (20) are removably mounted within the
20 housing (2).
31. A push button assembly according to any one of claims 21-30 wherein the strip (22) and/or the body (19) are completely within the confines of the housing (2).
32. A push button assembly according to any one of claims 1-31 wherein
25 the body (19) and/or strip (22) snaps onto a part of the housing (2) and

-18-

is held in place by pegs passing through the body (19) and the strip (22).

33. A push button assembly according to any one of claims 1-32 wherein the lamp (25) and switch (20) are connected to appropriate operating circuitry of an amusement or gaming machine.
- 5
34. An entertainment machine incorporating a push button assembly as described in any one of claims 1-33.




FIG. 1




FIG. 2




Fig. 3




Fig. 4

INTERNATIONAL SEARCH REPORT

Application No

/GB2005/003970

A. CLASSIFICATION OF SUBJECT MATTER

H01H13/02 H01H9/18

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

H01H G06F H02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 201 408 A (TORMA ET AL) 13 April 1993 (1993-04-13) column 3, line 18 - column 6, line 60; figures 1-3	1-7, 17-20, 29-34
Y		8-16
Y		21-28
Y	EP 1 091 374 A (OMRON CORPORATION) 11 April 2001 (2001-04-11) paragraph '0018! - paragraph '0036!; figure 2	8-13
Y	EP 0 406 845 A (OTIS ELEVATOR COMPANY) 9 January 1991 (1991-01-09) page 4, line 1 - page 6, line 25; figures 2b,4,5	8-13
	----- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

20 January 2006

Date of mailing of the international search report

31/01/2006

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Nieto, J.M.

INTERNATIONAL SEARCH REPORT

Application No

/GB2005/003970

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2002/144882 A1 (YAMAGUCHI TOSHINOBU) 10 October 2002 (2002-10-10) paragraph '0026! - paragraph '0029!; figure 1 -----	14-16
Y	EP 0 342 703 A (OMRON TATEISI ELECTRONICS CO; OMRON CORPORATION) 23 November 1989 (1989-11-23) column 8, line 19 - line 32; figures 1,2 -----	21-23
Y	EP 0 463 285 A (NIHON KAIHEIKI INDUSTRIAL CO., LTD) 2 January 1992 (1992-01-02) column 2, line 41 - column 5, line 4; figure 3 -----	26,27
Y	US 6 310 308 B1 (WATSON JEFFREY ET AL) 30 October 2001 (2001-10-30) column 3, line 24 - column 4, line 5; figure 1 -----	24,25,28

INTERNATIONAL SEARCH REPORT

Information on patent family members

Application No

/GB2005/003970

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5201408	A	13-04-1993	NONE	
EP 1091374	A	11-04-2001	AU 4392499 A CN 1312948 A DE 69911407 D1 DE 69911407 T2 ES 2207235 T3 WO 9967799 A1 JP 3644258 B2 JP 2000011793 A US 6417469 B1	10-01-2000 12-09-2001 23-10-2003 01-07-2004 16-05-2004 29-12-1999 27-04-2005 14-01-2000 09-07-2002
EP 0406845	A	09-01-1991	AU 630717 B2 AU 5867590 A DE 69005927 D1 DE 69005927 T2 FI 96249 B HK 90794 A JP 2815986 B2 JP 3179624 A US 5039832 A ZA 9003591 A	05-11-1992 10-01-1991 24-02-1994 05-05-1994 15-02-1996 09-09-1994 27-10-1998 05-08-1991 13-08-1991 27-03-1991
US 2002144882	A1	10-10-2002	CN 1380668 A JP 2002304934 A	20-11-2002 18-10-2002
EP 0342703	A	23-11-1989	AT 157194 T DE 68928261 D1 US 4968860 A US 5165530 A	15-09-1997 25-09-1997 06-11-1990 24-11-1992
EP 0463285	A	02-01-1992	JP 4025124 U US 5134505 A	28-02-1992 28-07-1992
US 6310308	B1	30-10-2001	NONE	